


# Scinor® SMT600-S26

## Submerged Ultrafiltration Module

Scinor SMT600 series ultrafiltration modules utilizing our state-of-the-art Thermally Induced Phase Separation (TIPS) PVDF membranes provide the highest permeability, mechanical strength, and chemical tolerance in the industry. These modules are ideal for use in potable water, wastewater, desalination, and industrial applications. The SMT600-S26 retrofits major membrane vendor installations giving end-users a choice when replacing membranes.

Scinor SMT600-S series submerged ultrafiltration modules are applied in vacuum operation during filtration mode. Due to the membrane's hydrophilic nature and the unique module design, the SMT600-S series can accept a wide-range of even the dirtiest water. To maintain stable operation at the required capacity, backwash with aeration is employed at regular intervals and chemical cleanings are utilized on an infrequent basis.



### Product Advantages

**Excellent Filtered Water Quality**

- >3.5 log virus removal and >6 log crypto removal
- Low fiber breakage rate

**Long Operational Life**

- High mechanical strength and durability
- >5000 mg/L Sodium Hypochlorite tolerance

**Low Requirements for Pretreatment**

- Open, immersed design

**Low Operating and Maintenance Requirements**

- Low energy and chemical consumption due to higher permeability
- Automatic operation

**Low Capital Cost**

- High flux rates on all water sources

**Small Footprint**

- High hollow-fiber packing density

Retrofit modules available for all major membrane suppliers

**Italhydro-Italy**

36016, Thiene (VI)  
Italy  
office@italhydro.com

Please visit [italhydro.com](http://italhydro.com) for further information.



Scinor® Module	Part Number	SMT600-S26
	Fiber Material	Polyvinylidene Fluoride (PVDF)
	Effective Area	280 ft <sup>2</sup> (26 m <sup>2</sup> )
	Nominal Pore Size	0.1 µm
	Fiber ID/OD	0.6 mm/1.1 mm
	Geometry	Φ131 mm × 1192 mm
	Housing/Head Material	PE/ABS
	Potting Material	Polyurethane
Operating Parameters	Temperature	33-104 ° F (1-40 C)
	pH Range	1-13
	Max. NaClO	5000 mg/L
	Backwash Flux	18-41 gfd (25-70 lmh)
	Air Scour Flow	3.1-7.5 scfm/module (5-12 Nm <sup>3</sup> /hr/module)
	Max. TMP	14 psi (0.085 MPa)
	Max. Backwash Pressure	21.2 psi (0.15 MPa)
	Turbidity	≤0.1 ntu
Filtered Water Performance	Silt Density Index	≤3
	E.Coli Removal	non-detect
	LRV, Virus	3.63
	LRV, Cryptosporidium	>6.0



Drinking Water



Wastewater



Desalination



Industrial